



Series	S-SERIES LFP	Warranty	See Warranty Terms
Volts	12	Design	8D
Terminal Type		M8	
Included Hardware		M8 stainless bolts & washers	
Charge Discharge			
Charge Voltage Range	14.0 - 14.6V		
Recommended End of Discharge Voltage	12.0 V		
End of Discharge Protection Voltage	10.0 V		
Recommended Charge Voltage	14.4 V		
Recommended Charge Current			
-20~0°C (-4~50°F)	0.1C	30A	
0~10°C (32~50°F)	0.2C	60A	
10~35°C (50~95°F)	0.5C	150A	
35~50°C (95~122°F)	0.2C	60A	

Charge Mode:

- Charge at recommend voltage & current by temperature until charge current drops to $\leq 0.05C$ (CC,CV)
- DO NOT USE TEMPERATURE COMPENSATION
- No BTS (Battery Temperature Sensor)

Max Continuous Charge Current	200 A
Max Continuous Discharge Current	200 A
Surge Current Limit	1100 A (300ms)
Charge Temperature Range	-20°C~55°C (-4~131°F)
Discharge Temperature Range	-20°~60°C (-4~140°F)
Storage Temperature Range	-5°~45°C (23~113°F)

Capacity	
Nominal Capacity	300 AH
Total Energy	3.84 kWh
Nominal Voltage	12.8 V

Safety

- Cylindrical LiFePO4 cells [ITR26-70/46E 4.6Ah, 26700] (UL1642)
- IEC62133 (cell), IEC62619(cell), UN38.3 (cell/pack)
- ROHS (cell), CE system certification, IP65 Rating

Design

- Standard-size (BCI) ABS container for easy VRLA replacement
- Fast charge/discharge performance
- Display & integrated controls
- Visual state-of-charge (SOC)
- External fuse access
- Internal heating for -20°C (-4°F) to 0°C (32°F) charging *
- Bluetooth Connectivity & dedicated IOS & Android App
- Maintenance-free operation

* Note: When connected in series, internal heating may increase charge imbalance requiring external rebalancing.

Refer to [R-Series & S-Series LFP Battery Operating Manual](#)

Battery Management System (BMS)

- Integrated hardware BMS inside
- Independent charge & discharge protection
- Balance Protection
- Short-Circuit Protection, Over-Voltage Protection, Low-Voltage Protection, Over-Current Protection, Low-Temperature Protection, Over-Temperature Protection

[12V LFP Profile](#)

Specifications		
Weight	30.5 kg	67.2 lbs
Length	522 mm	20.55"
Width	268 mm	10.55"
Height	219 mm	8.62"
Height Incl. Term.	232 mm	9.13"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Rope / Plastic Handle
Internal BMS Model	4S200ATX-V2
Expected Cycle Life	>6000 @ 80% DOD, >3000 @ 100% DOD
Series Connection	4 UNITS MAX (48V)
Parallel Connection	4 UNITS MAX (48V) or 6 UNITS MAX (12V)
Connectivity	Up to 4S4P (in 48V configuration) or 1S6P (in 12V configuration)

