



Series	R-SERIES LFP	Warranty	See Warranty Terms
Volts	24	Design	Grp 24
Terminal Type	M8		
Included Hardware	M8 stainless bolts & washers		
Charge Discharge			
Charge Voltage Range	28.0 - 29.2V		
Recommended End of Discharge Voltage	24.0 V		
End of Discharge Protection Voltage	20.0 V		
Recommended Charge Voltage	28.8 V		
Recommended Charge Current			
0~10°C (32-50°F)	0.2C	10A	
10~35°C (50-95°F)	0.5C	25A	
35~50°C (95-122°F)	0.2C	10A	
Charge Mode:			
<ul style="list-style-type: none"> Charge at recommend voltage & current by temperature until charge current drops to $\leq 0.05C$ (CC,CV) DO NOT USE TEMPERATURE COMPENSATION No BTS (Battery Temperature Sensor) 			
Max Continuous Charge Current	25 A		
Max Continuous Discharge Current	50 A		
Surge Current Limit	400 A (300ms)		
Charge Temperature Range	0°C~55°C (32~131°F)		
Discharge Temperature Range	-20°~60°C (-4~140°F)		
Storage Temperature Range	-5°~45°C (23~113°F)		
Capacity			
Nominal Capacity	50 AH		
Total Energy	1.28 kWh		
Nominal Voltage	25.6 V		

Safety

- Cylindrical LiFePO4 cells [ITR26-70/40E 4Ah, 26700] (UL1642)
- IEC62133 (cell), IEC62619(cell), UN38.3 (cell/pack)
- ROHS (cell), CE system certification, IP65 Rating

Design

- Standard-size (BCI) ABS container for easy VRLA replacement
- Fast charge/discharge performance
- Maintenance-free operation
- Bluetooth Connectivity & dedicated IOS & Android App

Battery Management System (BMS)

- Integrated hardware BMS inside
- Independent charge & discharge protection
- Short-Circuit Protection, Over-Voltage Protection, Low-Voltage Protection, Over-Current Protection, Low-Temperature Protection, Over-Temperature Protection

24V LFP Profile

Specifications		
Weight	12 kg	26.5 lbs
Length	260 mm	10.24"
Width	170 mm	6.69"
Height	208 mm	8.19"
Height Incl. Term.	211 mm	8.3"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

Container	ABS
Cover	ABS
Handles	Integrated Top Mount
Internal BMS Model	8S50A
Expected Cycle Life	>6000 @ 80% DOD, >3000 @ 100% DOD
Series Connection	2 UNITS MAX (48V)
Parallel Connection	4 UNITS MAX (48V) or 6 UNITS MAX (24V)
Connectivity	Up to 2S4P (in 48V configuration) or 1S6P (in 24V configuration)

Detailed Illustration

